



CV. GLOBAL KARUNIA TECHNOLOGY

Office Equipment and Computer

Jl. Mangga Buntu No. 35 Semarang Telp : 024 - 76440076

Email : gktsmrg@yahoo.com

Nomor : 023/GKT-SMG/IX/2021

Semarang, 30 September 2021

Lampiran : -

Kepada Yth.
Pejabat Pembuat Komitmen
UIN Walisongo
di
Semarang

Perihal : Permohonan Pembayaran

Berdasarkan Surat Perjanjian Kerja /Kontrak Nomor : 1929/Un.10.8/D/PL.01.02/06/2021 Tanggal 3 Juni 2021 disampaikan dengan hormat bahwa pelaksanaan Pengadaan Alat – Alat Laboratorium MIPA Pada Fakultas Sains dan Teknologi UIN Walisongo Semarang selesai 100 % (Seratus persen).

Sehubungan dengan hal tersebut diatas kami mohon untuk dilakukan pembayaran pelaksanaan pekerjaan tersebut sebesar Rp 835,890,000,- (Delapan Ratus Tiga Puluh Lima Juta Delapan Ratus Sembilan Puluh Ribu Rupiah).

Pembayaran tersebut dapat ditransfer melalui rekening perusahaan kami pada Bank Jateng Dengan data sebagai berikut :

Nama Rekening : CV. Global Karunia Technology

Nama Direktur : Marsini

Nomor Rekening : 1.034.00954.2 Bank Pembangunan Daerah Jateng Cabang Utama

NPWP : 02.798.956.5-508.000

Demikian Permohonan ini kami buat dan atas perhatiannya diucapkan terima kasih.

Hormat Kami,
CV. Global Karunia Technology



MARSINI

Direktur

SURAT KETERANGAN BANK

Nomor :916/PLY.01/034/2020

Yang Bertanda tangan dibawah ini menerangkan bahwa :

Nama : **CV. GLOBAL KARUNIA TECHNOLOGY**
Alamat : **Jl. Mangga Buntu No 35, Semarang**
Direktur : **Marsini**

Adalah nasabah PT Bank Pembangunan Daerah Jawa Tengah Cabang Utama :

Sejak Tanggal : **08 April 2010**
Nomor Rekening : **1.034.00954.2**

Surat Keterangan ini tidak mempunyai ikatan apapun dengan pihak Bank serta batal dengan sendirinya apabila penggunaannya menyimpang dari yang dimaksud diatas.

Demikian untuk menjadikan maklum.

Semarang, 04 Januari 2021
PT BANK PEMBANGUNAN DAERAH
JAWA TENGAH
Cabang Utama

AMRINA ROSYADA
Pjs. Pemimpin Bidang Pelayanan



**DEPARTEMEN KEUANGAN REPUBLIK INDONESIA
DIREKTORAT JENDERAL PAJAK**

NPWP : 02.798.956.5-508.000

NAMA : CV. GLOBAL KARUNIA TECHNOLOGY

**ALAMAT : JL. MANGGA BUNTU NO.35 RT.004
RW.006,
LAMPER KIDUL, SEMARANG SELATAN,
SEMARANG,
JAWA TENGAH**

**TERDAFTAR
02/02/2010**

508

Faktur Pajak

Kode dan Nomor Seri Faktur Pajak : 020.004-21.15991216		
Pengusaha Kena Pajak		
Nama : CV GLOBAL KARUNIA TECHNOLOGY Alamat : JL MANGGA BUNTU NO 35 RT 004 RW 006 , KOTA SEMARANG NPWP : 02.798.956.5-508.000		
Pembeli Barang Kena Pajak / Penerima Jasa Kena Pajak		
Nama : UNIVERSITAS ISLAM NEGERI WALISONGO SEMARANG DITJEN PENDIDIKAN ISLAM Alamat : JL. WALISONGO Blok 000 No.3-5 RT:000 RW:000 Kel.TAMBAKAJI Kec.NGALIYAN Kota/Kab.SEMARANG JAWA TENGAH 00000 NPWP : 00.146.243.1-503.000		
No.	Nama Barang Kena Pajak / Jasa Kena Pajak	Harga Jual/Penggantian/Uang Muka/Termin
1	Pengadaan Alat-Alat Laboratorium MIPA Pada Fakultas Sains dan Teknologi UIN Walisongo Tahun 2021 Rp 759.900.000 x 1	759.900.000,00
Harga Jual / Penggantian		759.900.000,00
Dikurangi Potongan Harga		0,00
Dikurangi Uang Muka		0,00
Dasar Pengenaan Pajak		759.900.000,00
PPN = 10% x Dasar Pengenaan Pajak		75.990.000,00
Total PPnBM (Pajak Penjualan Barang Mewah)		0,00

Sesuai dengan ketentuan yang berlaku, Direktorat Jenderal Pajak mengatur bahwa Faktur Pajak ini telah ditandatangani secara elektronik sehingga tidak diperlukan tanda tangan basah pada Faktur Pajak ini.

KOTA SEMARANG, 27 September 2021



CV GLOBAL KARUNIA TECHNOLOGY



CV. GLOBAL KARUNIA TECHNOLOGY

Office Equipment and Computer

Jl. Mangga Buntu No. 35 Semarang Telp : 024 - 76440076

Email : gktsmrg@yahoo.com

Nomor : 020/GKT-SMG/IX/2021
Lampiran : 1 (Satu Bendel)

Semarang, 30 September 2021

Kepada Yth.
Pejabat Pembuat Komitmen
UIN Walisongo
di
Semarang

Perihal : Permohonan Pemeriksaan dan Penerimaan
Hasil Pekerjaan

Dengan Hormat,

Berkaitan dengan pelaksanaan Pengadaan Alat – Alat Laboratorium MIPA Pada Fakultas Sains dan Teknologi UIN Walisongo Semarang dipercayakan kepada CV. Global Karunia Technology dengan Surat Perjanjian Kerja /Kontrak Nomor : 1929/Un.10.8/D/PL.01.02/06/2021 Tanggal 3 Juni 2021.

Sehubungan dengan hal tersebut diatas kami mohon diadakan Pemeriksaan dan Penerimaan Pekerjaan Pengadaan barang tersebut di atas.

Demikian Surat Permohonan ini, atas perhatiannya kami ucapkan terima kasih.

Hormat Kami,
CV. Global Karunia Technology

MARSINI

Direktur



CV. GLOBAL KARUNIA TECHNOLOGY

Office Equipment and Computer

Jl. Mangga Buntu No. 35 Semarang Telp : 024 - 76440076

Email : gktsmrg@yahoo.com

FAKTUR PENGIRIMAN
PENGADAAN ALAT – ALAT LABORATORIUM MIPA PADA FAKULTAS SAINS DAN TEKNOLOGI UIN
WALISONGO TAHUN 2021

No	Nama Barang	Spesifikasi	Merk Dan Type	Jumlah	Paraf
1	Instant Connect Flame Ionization Detector	Capillarycolumn optimized compatible with 1/8" and 1/16" packed column, Flameout detection and automatic re-ignition, Minimum Detectable Level (MDL) : <1.4 pg C/s, Sensitivity : >0.03 Coulombs/gC, Linear dynamic range : >107 ($\pm 10\%$), Maximum temperature : 450 °C in steps of 0.1 °C, IEC : Air: 0–500 mL/min in 0.1 steps, H ₂ : 0– 100 mL/min in 0.1, Completed with : Gas Nitrogen UHP (N ₂) Purity 99,999 and Cylinder 1 Pressure Regulator N ₂ 1, Gas Hydrogen UHP (H ₂) Purity 99,999 and Cylinder 1, Pressure Regulator H ₂ 1, Oil less air compressor 1, Mist Separator kit 1, Carrier Gas Supply pipe 1, Base Plate for 3 filters 1, 3 Cartridge Pack – contains 1 x Triple Filter and 2 x Combi Filter"	Genecraft	1	
2	Labtron LUHS-A10	Ultrasonic power 10 to 150 W Disruption capacity 0.2 to 150 ml Standard horn/probe Ø 6 mm Display LCD display Optional probe/horn Ø2, Ø3, Ø8 mm Operating frequency 20- 25 KHz, Automatic Tracking Temperature control range RT to 100°C Unit details Host + Sound proof Box + Horn Storage memory 50 sets Duty cycle 0.1 - 99.9% Total working time 1 to 999.9 min Packaging Dimension (Host machine + accessories) 490 x 460 x 310 mm Packaging Dimension (Sound proof enclosed box) 570 x 370 x 370 mm Packaging Gross Weight (Host machine + accessories) 15.85 kg Packaging Gross Weight (Host machine + accessories) 9.45 kg Power Supply 220/110 V HS Code 8479820090	Labtron	1	
3	Memmert Oven UN30	Type UN 30 Textured Stainless Steel Casing w x h x d: 585 x 707 x 434 mm fully insulated stainless steel door with 2-point locking (compression door lock) rear zinc-plated steel Interior - Heating Concept w x h x d: 400 x 320 x 250 mm, 32 l easy-to-clean interior, made of stainless steel, reinforced by deep drawn ribbing with integrated and protected large-area heating on four sides 1 stainless steel grid Max. loading of chamber: 60 kg Temperature Range min. 5°C above ambient up to +300°C Voltage / Power Rating	Memmert	1	

		<p>230 V (+/- 10%), 50/60 Hz / approx. 1.600W 115 V (+/- 10%), 50/60 Hz / approx. 1.600 W</p> <p>Packing Data net weight approx. 48 kg gross weight carton approx. 59 kg dimensions approx.: carton w x h x d: 69 x 96 x 66 cm the appliances must be transported upright</p>			
4	pH meter Lutron PH 220	<p>Type PJ-220 Separate pH electrode, easy for general purpose and remote measurement 0 to 14.00 pH Auto calibraton for pH 4, pH 7, or pH 10 Temp. adjustment is not necessary IP-65 water proof Pen type, easy carry out Complete set with separate pH electrode (pe-11) and pH 4, pH 7 standard solution Build in reverse displaybutton DC 1.5 V Battery (UM-4, AA) x 4, long life</p>	Lutron	1	
5	Purelab Quest PQDIUVM 1	<p>Purelab QUEST (Can Produce Type 1,2 and 3) PURELAB QUEST Water Purifier conforms to international water standard (CLSI, CLRW, ISO 3696, ASTM D1193-06, Pharmacopeia, USP, EP, & JP) Specifications : Type 1 Resistivity : 18.2 MΩ.cm@ 25oC Flow rate : Up to 1.2 l/min Recommended volume : Up to 10 l/day TOC value : < 5 ppb Bacteria TVC : 1MΩ.cm @ 25oC Recommended volume : Up to 10l/day TOC value :</p>	Purelab	1	
6	Ohaus Pioneer PX224E	<p>"Combining Economy and High Performance for Essential WeighingThe Pioneer PX Series combines essential weighing functionality with competitive performance, offering high accuracy and repeatability for applications in laboratory, industrial and education settings. The PX is affordably priced, and intuitively designed for intelligent operation with a second line display for additional information, and USB and RS232 connectivity for easy communication. Standard Features Include:•Competitive Performance at an Economical PriceThe PX offers high accuracy and repeatability for essential weighing applications in laboratory, industrial and education settings at an economical price point.•Durably Constructed for Long-Term UseFeaturing a cast metal lower housing, sub-pan and stainless steel weighing pan,the PX is durably constructed for versatile, long-term use.•Designed for Simple, Intelligent OperationThe PX features a second line display for additional information or guidance, a static removal bar for convenient grounding, a capacity bar which displays the progress of the weighing, and USB and RS232 connectivity for easy communication."</p>	Ohaus	1	

7	Rotary Evaporator DLAB-RE100 PRO	<p>Digital display for both rotation speed and heating temperature allows for optimal controlling of all distillation processes</p> <p>Motor lift automatic release the evaporating flask to a safety position in case of power failure</p> <p>Wide temperature range of the 5L heating bath (Room temp. to 180 °C), Overheating protection temperature at 220°C Speed range from 20 to 280 rpm, and interval operation in clockwise and anticlockwise directions for drying process</p> <p>Patented condenser (cooling surface 1,500 cm²) with excellent cooling effect</p> <p>Ejection mechanism ensures easy removal of evaporating flask</p> <p>Patented double spring sealing ring which made of PTFE provides an excellent sealing performance</p> <p>Remote function provides PC control and data transmission</p>	DLAB	1	<i>Ans</i>
8	Vacuum Pump + circulating water for (rotary evaporator) B-ONE SHB-III	<p>Kecepatan Sirkulasi Air: 80 L / Menit</p> <p>Maksimum Vacuum: -0.098 Mpa (20mbar)</p> <p>Voltage: 220 V</p> <p>Daya: 180watt</p> <p>Kecepatan Vacuum (1 Tap): 10L/menit</p> <p>Jumlah Tap: 2</p> <p>Panjang Max Sirkulasi Air: 10m Kapasitas Tangki Air: 15L Material Tanki Air: PP</p> <p>Dimensi (p x l x t): 385 x 280 x 420 (mm)</p> <p>Berat: 11 kg</p> <p>Lapisan: PP Ejector: PP Tee: PP</p> <p>Check Valve: PP Nozzle Hisap: PP Body</p> <p>Pompa: SS 304 Impeller: 304</p> <p>Connecting Pipe: NR</p>	B-One	1	<i>Ans</i>
9	Therma Scientific Lead Data Coded Hollow Cathode Lamp	Lead Data Coded Hollow Cathode Lamp for AAS ICE 3000 series, p/n: 942339030821	Genecraft	1	<i>Ans</i>
10	Therma Scientific Cadmium Data Coded Hollow Cathode Lamp	Cadmium Data Coded Hollow Cathode Lamp for AAS ICE 3000 series, p/n: 942339030481	Genecraft	1	<i>Ans</i>
11	Neraca Scout STX 222	<p>Maximum capacity: 220 g Readability: 0.01 g</p> <p>Pan Size: 4.7 in (120 mm)</p> <p>Battery Life: 6 Hours with disposable batteries</p> <p>Communication: RS232 (Available as an Accessory); ; USB Host (Available as an accessory); USB Device (Available as an Accessory); Ethernet (Available as an Accessory); Bluetooth (Available as an Accessory)</p> <p>Dimensions: 2.1 in x 8.8 in x 8 in (54 mm x</p>	Ohaus	3	<i>Ans</i>

		<p>224 mm x 202 mm) (HxLxW) Display: Full-Color 4.3 in Touchscreen WQVGA In-use cover: Available as an Accessory Legal for Trade: Not Applicable Linearity ± 0.01 g Net Weight: 2.2 lb (1 kg) Pan Construction: Stainless Steel Power: AC Adapter (Included); 4AA (LR6) Batteries (Not Included) Repeatability (typical): 0.01 g Stabilization Time: 1s Tare Range: To capacity by subtraction Transportation Case: Available as and Accessory Units of Measurement: Carat; Custom; Grain; Gram; Milligram; Newton; Ounce; Ounce Troy; Pennyweight Working Environment: 50°F - 104°, 80%RH, non-condensing (10°C - 40°C, 80%RH, non-condensing) Auxiliary Display Model: Available as an Accessory</p>			
12	DLAB Micropipette Plus Single Channel Variable vol 100 - 1000 uL	<p>Range: (100 – 1000 uL) Fully autoclavable at 121°C Lightweight and ergonomic design Integral tip ejector for access into narrow tubes Easy to calibrate and maintain with tool supplied</p>	DLAB	1	<i>Ant</i>
13	UPS Prolink PRO 2000 SFCU	<p>Type: PRO2000 SFCU Capacity: 2000VA / Up to 1400 Watt; Input Power Voltage : 170 ~ 280V, Frequency Range 50Hz/60Hz (auto sensing), Phase : Single + GND; Back-Up Time : 8~40 Minutes (depending on load), Recharge Time 2 - 4 hours recover to 90% capacity;</p>	Prolink	4	<i>JMN</i>
14	OPS PC Module benQ OPS IE1002	<p>CPU: Intel Kaby lake-U I5 7200U, TDP 15W RAM: DDR4 8G (4GB x2), SSD: 128 GB, Graphics: Intel HD Graphics 620, RJ-45, WIFI, Embedded PC Module Windows 10 Pro</p>	BenQ	1	<i>JMN</i>
15	Krisbow Gergaji Scroll 90 W Scrol Saw	<p>Daya motor : 90 Watt, Material body : cast iron, Dilengkapi penutup cover, Tegangan listrik : 230V, 50Hz, Kecepatan : 550-1600 RPM, Stroke :1,5 cm, Ukuran meja : 41,5 x 25,5 cm, Panjang pisau : 12,5 cm, Dimensi produk : 57.5 x 31 x 37.5 cm</p>	Krisbow	1	<i>JMN</i>

16	Mesin Gergaji Jigsaw Makita 4329	Daya Listrik : 450 Watt, Jenis Mata : T-Shank, Kapasitas Potong Kayu : 65mm, Kapasitas Potong Besi : 6 mm, Panjang Gerakan Potong : 18mm, Gerakan Potong : 500 - 3100 per menit, Fitur : Gerakan Pisau seperti Pendulum, Variable Speed	Makita	1	
17	Krisbow Cordless Impact Drill 13mm 18V + Ekstra Battery IRCD 181	Nett Weight: 3.52 kg Dimension Unit: 39.5X12X32CM Benefit : Easy and effective to use portable without electric source Features: Compact & light weight design, Single sleeve chuck with automatic spindle lock, Equipped LED light Specification: Chuck capacity (mm) : 13 (keyless), Max drilling Steel (mm) : 10 ; wood (mm) 38 Item: Cordless Drill Battery : 18 VDC Speed: 0-350/0-1200 Rpm Torque: 22 ~ 35 Nm Lithium Ion Battery + Ekstra Battery 18V 2.0ah IRAB182	Krisbow	1	
18	2 In 1 Blower Vacuum Cleaner Penghilang Debu Komputer	Product Material: ASBmetal, Color: Yellow and black, Velocity Without Load: 13000r/min, Frequency: 50/60HZ, Plug: EU plug 220V, Package weight: 2726g/96.1oz, Package Size: 37.52421cm/14.79.48.2in, Packing List: 1 Dust Blower; 1 Collection Bag; 2 Wind Noses; 2 Connecting Tubes; 1 Dust Tube	N/A	1	
19	Bosch GAS 18V-1 Professional	Container volume, gross: 0.7 l; Length: 452 mm; Width: 120 mm; Filter surface: 123 cm; Max. airflow: 19.3 l/sec; Max Volume : 700 mL; Max. ventilating pressure: 60 mbar; Battery voltage: 18 V; Include: -1 unit Baterai 18V Bosch (4.0 mAh), -1 unit Charger 1860 CV Bosch, -nozzle sesuai dengan gambar produk; Garansi Resmi 1 Tahun Bosch	Bosch	1	
20	Contec EEG Machine KT88	16 channels of EEG +2 channels of ECG (ECG is optional) Sampling Rate : 100dot/s Accuracy : 12bit Input Impedance : $\geq 10M\Omega$ Patient Leak Current : $< 10\mu A$ Noise Level : $\leq 5\mu Vp-P$ CMRR : $\geq 90dB$ Magnification Multiple : 10000 Filter Constant : All digital and free anactment Display speed(paper speed) : 5, 10, 15, 30, 60, 120 mm/s Amplitude : 1. 1.5, 2, 3, 5, 7.5, 10, 12, 15, 20, 30, 50 mm/50 μV Playback Speed : 1 time, 2 times, 3 times, 10 times, 20 times, 40 times, 60 times 50Hz interference suppression : $\geq 30dB$ Safety type : Class II, type BF applied part	EEG	1	

21	SET Teleskop Bintang Computerized Telescope	<ul style="list-style-type: none"> • Focal Length : 1500mm (59") • Focal Ratio : f/12 • Focal Length of Eyepiece 1 : 25mm (0.98") • Magnification of Eyepiece 1 : 60x • Focal Length of Eyepiece 2 : 9mm (0.35") • Magnification of Eyepiece 2 : 167x • Finderscope : StarPointer red dot finderscope • Star Diagonal : 1.25 • Optical Tube : Aluminum • Highest Useful Magnification : 300x • Lowest Useful Magnification : 18x • Limiting Stellar Magnitude : 13 • Resolution (Rayleigh) : 1.1 arc seconds • Resolution (Dawes) : 0.91 arc seconds • Light Gathering Power (Compared to human eye) • Optical Coatings : Fully-Coated • Optical Tube Length : TBD • Optical Tube Diameter : TBD • Optical Tube Weight : TBD • Dovetail : CG-5 Dovetail bar • Mount Type : Computerized Altitude-Azimuth Single Fork Arm • Instrument load capacity : 8 lbs (3.6kg) • Height adjustment range (includes mount and tripod) : 762mm - 1270mm (30" - 50") • Tripod Leg Diameter : 31.75mm (1.25") Stainlesssteel • Mount Head Weight : 5 lbs (2.3kg) • Accessory Tray : Yes • Tripod Weight : 5 lbs (2.3kg) • Slew Speeds : 9 slew speeds - max speed 3°/second • Tracking Rates : Sidereal, Solar and Lunar • Tracking Modes : Alt-Az, EQ North and EQSouth • GPS : N/A • Dovetail Compatibility : CG-5 saddleplate Number of Auxiliary ports : 1x Aux port 1x hand control port (hand control can use 	Celestron	1	
22	Nuclear Radiation Tester Radiasi Nuklir	<p>Gelombang yang bisa diuji: Beta, Gamma, X-Ray</p> <p>Tipe sensor: GM tube</p> <p>Rentang energi: 50keV-1.5MeV less than 30%</p> <p>Relative intrinsic error of less than plus or minus 10%</p> <p>Sensitivitas: 80cpm / USV / Co-60</p> <p>The maximum dose equivalent rate: 99.99usv/h</p> <p>The use of ambient temperature -25 +45</p> <p>Relative humidity less than 95%</p> <p>Power supply: 2 buah baterai AA, dapat didukung oleh port USB ketika Anda perlu waktu pemantauan jangka panjang</p>	BR-6	7	

23	Agate Mortar With Pestle Lab Glassware Mixing Grinder	Color: Purple Material: Agate Inner Dia.: 60mm Uses: Laboratory sample pretreatment of solid powder hand grinders for grinding and analysis of solid materials or for the mixing of powdered solids. Features:- The product has no cracks, no impurities and strong abrasion resistance;- The product has high gloss and corrosion resistance and can be used in acidic abrasive materials;- Made from imported Brazilian raw materials, with high purity and hardness, all meet the quality technical standards;- Healthy and easy to carry; -Our natural agate mortar and grinding is literally rock hard, is non-porous, will not absorb flavors and odours, and its matte surface creates friction for grinding but is smooth enough to wipe clean easily;- Mortar and Pestle Set Made from Agate, for grinding items into a fine paste or powder;- Make aromatic dry rubs, curry pastes, pestos, nut butters, ground cinnamon or grind peppercorns, prepare holistic remedies, pulverize pills, and more;- Great for Grinding Herbs, Spices, Nuts and Seeds to release their Aroma;- Easy to use and clean, safe for easy cleanup;- Suit for home or labs. Package Included: 1 Pcs x Agate Mortar 1 Pcs x	N/A	1	
24	Handycam FDR- AX700 4K Camcorder	1" - Type Stacked CMOS Sensor Bionz X Image Processor 4K HDR Video Recording 0.39" OLED EVF 3.5" XtraFine LCD Zeiss Vario Sonnar T* Lens 12x Optical Zoom & 18x Clear Image Zoom Optical SteadyShot Image Stabilization 273-Point Phase Detection Autofocus Built-in Wifi with NFC Unit Utama	Sony	2	
25	Tripod Libec 650 Ex	Payload 3kg Counterbalance Fixed Ball diameter 65mm Section 2 Stage Slide plate compatible with Libec TH-X Improved tripod leg lock Unit Utama	Libec	1	
26	Mic Wireless Clip On Hardwell C-2	Type: C-2 Frequency response 20 Hz s/d 14KHz Sensitivity -44±3dB Impedance: 1000Ω 30% Dimension: 475x345x390 mm Weight: 160g	Hardwell	2	

Semarang, 23 September 2021
CV. Global Karunia Technology


MARSINI
Direktur